

MAPETROL ANTI-FREEZE DIESEL**Description:**

Mapetrol Anti-Freeze Diesel enhances the capacity of diesel to flow smoothly in colder operating conditions. It ensures diesel fuel's winter suitability and safeguards it against the formation of crystals or freezing.

Benefits:

- Ensures diesel fuel's suitability for winter conditions
- Halts the formation of wax crystals and confines their size when temperatures drop
- Averts gel formation and instances of sluggish or blocked flow in filters, valves, injectors and the entire fuel system.
- Lowers the cold filter plugging point by as much as 12 °C, depends upon the composition of the treated diesel fuel
- Thwarts the settling and aggregation of wax crystals at the base of the fuel tank
- Safeguards the fuel system from deterioration, rust, and corrosion

Usage:

Applicable to all diesel engines, including those equipped with common rail technology, whether turbocharged or not. Designed for operation with both low and standard levels of sulfur (bio)diesel fuels. Ensures fuel is winter-safe.

Instructions:

- Dosage: Various treatment ratios are available, contingent upon the specific formulation (from 1:167 up to 1:1000 litres of diesel fuel)
- Before adding diesel empty the required contents of a bottle into the fuel tank
- Use before initial wax crystals build-up
- It is suggested to employ one bottle for each tank filling

Technical specification:

Colour	CLEAR TO HAZY
Smell	CHARACTERISTIC
Flash point [°C]	> 61
Density [g/cm ³]	0.888

