

Technical Data for:

MAPETROL PREMIUM DRIFT WS2+5W-50

Description:

Mapetrol Premium Drift WS2+ 5W-50 is fully synthetic lubricant, meticulously formulated with premium base oils and enhanced with WS2+ for superior performance and engine longevity. It is designed for sports cars, competition, and high-powered engines, where performance and protection are of utmost importance.

Benefits with WS2+ enhancement:

- High viscosity at hot engine
- WS2+ contributes to reduced friction within your engine, which translates into better fuel efficiency and prolonged engine life
- WS2+ minimizes wear, reducing maintenance costs
- Excels in maintaining engine cleanliness and safeguarding critical components
- Optimized engine efficiency, leading to reduced fuel consumption, thereby helping you save on fuel expenses
- WS2+ esures that your engine operates at the highest level of precision and protection

Specifications and approvals:

ACEA A3/B4 API SN/CF MB 229.3 BMW LONGLIFE-01 VW 501 01/505 00

Typical characteristics:

| Test | Method | Unit | Results |
|-------------------------------|-------------|----------|---------|
| Density at 15 °C | ASTM D 4052 | [g/cm3] | 0.85 |
| Kinematic viscosity at 40 °C | ASTM D 445 | [mm2/s] | 109 |
| Kinematic viscosity at 100 °C | ASTM D 445 | [mm2/s] | 17.8 |
| Viscosity index | ASTM D 2270 | - | 180 |
| Pour point | ASTM D 97 | [°C] | -39 |
| Flash point (Cleveland) | ASTM D 92 | [°C] | 225 |
| T.B.N. | ASTM D 2896 | mg KOH/g | 10.7 |

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

