

Technical Data for:

MAPETROL PREMIUM MOTOCROSS WS2+ 2T

Description:

Mapetrol Premium Motocross WS2+ 2T is fully synthetic engine oil, meticulously formulated and fortified with nanosized WS2+.

Benefits with WS2+ enhancement:

- Minimizes friction and heat, resulting in superior engine efficiency and power output
- WS2+ technology significantly extends the life of your engine, ensuring it can withstand the most demanding racing conditions
- Reduces friction and vibrations
- WS2+ esures that your engine operates at the highest level of precision and protection

Specifications and approvals:

API TC JASO FD ISO-L-EGD

Typical characteristics:

| Test | Method | Unit | Results |
|-------------------------------|-------------|----------|---------|
| Density at 15 °C | ASTM D 4052 | [g/cm3] | 0.873 |
| Kinematic viscosity at 40 °C | ASTM D 445 | [mm2/s] | 47 |
| Kinematic viscosity at 100 °C | ASTM D 445 | [mm2/s] | 8.8 |
| Viscosity index | ASTM D 2270 | - | 169 |
| Pour point | ASTM D 97 | [°C] | -32 |
| Flash point (Cleveland) | ASTM D 92 | [°C] | 129 |
| T.B.N. | ASTM D 2896 | mg KOH/g | 2 |

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.