

Technical Data for:

MAPETROL CLASSIC SCOOTER 4T 10W-40

Description:

Mapetrol Classic Scooter 4T 10W-40 is semi-synthetic, four-stroke, scooter engine oil that ensures a seamless and steady ride, thanks to its consistent blend of mineral and synthetic base oils combined with an advanced additive package. It is designed for use in the engines, transmissions, and wet clutches of four-stroke scooters.

Benefits:

- Prolongs the lifespan of your motorcycle by harnessing the oil's protective qualities
- Preserves the original riding comfort
- The oil's extensive applicability simplifies fluid management

Specifications and approvals:

API SI JASO MA2

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm3]	0.851
Kinematic viscosity at 40 °C	ASTM D 445	[mm2/s]	90
Kinematic viscosity at 100 °C	ASTM D 445	[mm2/s]	14
Viscosity index	ASTM D 2270	-	160
Pour point	ASTM D 97	[°C]	-36
T.B.N.	ASTM D 2896	mg KOH/g	6.1

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

