

MAPETROL PROFESSIONAL V 0W-20**Description:**

Mapetrol Professional V 0W-20, approved by Volvo, is a fully synthetic, fuel-efficient engine oil specifically developed for the latest gasoline and diesel passenger Volvo cars requiring Volvo VCC RBS0-2AE approval. This product boasts an ultra-low viscosity grade, designed to meet and exceed predetermined fuel-economy goals. The specialized formulation establishes a resilient layer that adeptly absorbs harmful particulates, ensuring the engine's sustained cleanliness and robust protection.

Benefits:

- Ensures optimal engine performance and longevity
- Enhances fuel efficiency
- Provides superior engine protection
- Excellent fluidity at low temperature
- Reduces CO2 emissions

Specifications:

ACEA C5, C6

API SN Plus, SN/RC, SP, SP/RC

Approvals:

Volvo VCC RBS0-2AE

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.845
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	40.64
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	8.06
Viscosity index	ASTM D 2270	-	176
Flash Point	ASTM D 92	[°C]	210
Pour point	ASTM D 97	[°C]	-57
T.B.N.	ASTM D 2896	mg KOH/g	7.7

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

