

MAPETROL PROFESSIONAL LL IV 0W-20**Description:**

Mapetrol Professional LL IV 0W-20, approved by Volkswagen Group, is a fully synthetic motor oil engineered for peak performance in modern Volkswagen Group gasoline and diesel engines. It is designed for use in passenger cars where VW 508 00/509 00 approval is required. Boasting an ultra-low viscosity, this product minimizes friction within the engine and lowers oil resistance, further optimizing its suitability for short-distance drivers.

Benefits:

- Reduces friction
- Enhances fuel efficiency
- Optimizes engine performance
- Minimizes deposit accumulation
- Provides top-tier protection and maintains peak performance even under demanding driving conditions

Specifications:

ACEA C5, C6

API SP, SN Plus

Approvals:

Approved VW 508 00/509 00

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.843
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	40.2
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	8.2
Viscosity index	ASTM D 2270	-	184
Flash Point	ASTM D 92	[°C]	235
Pour point	ASTM D 97	[°C]	-51
T.B.N.	ASTM D 2896	mg KOH/g	8.3

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

