

MAPETROL PROFESSIONAL LL III 0W-30**Description:**

Mapetrol Professional LL III 0W-30, approved by Volkswagen Group, is a fully synthetic, premium-performance engine oil, specifically developed for modern Volkswagen Group gasoline and diesel engines with a diesel particulate filter. It is designed for use in passenger cars where VW 504 00/507 00 approval is required. Thanks to long-term stability, reduced ash content and viscosity index 0W-30 this oil extends change intervals and saves fuel.

Benefits:

- Reduces fuel consumption
- Reduces CO2 emissions
- Protects engine parts by reducing friction and wear

Specifications:

ACEA C2, C3

API SN

Approvals:

Approved VW 504 00/507 00

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.842
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	59.0
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	11.7
Viscosity index	ASTM D 2270	-	197
Pour point	ASTM D 97	[°C]	-48
T.B.N.	ASTM D 2896	mg KOH/g	8.3

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

