

Technical Data for:**MAPETROL SPARCO SPORT 0W-40****Description:**

Mapetrol Sparco Sport 0W-40 is a high-quality, fully synthetic motor oil designed to meet the rigorous standards of German automakers. This unique formulation utilizes PAO for superior performance. It is designed for a wide range of gasoline and diesel engines in various European and other manufacturers' vehicles. Meets API SN/CF and ACEA A3/B4 standards. It is recommended for MB, BMW, and VW vehicles with additional oil requirements. Not suitable for heavy trucks or similar vehicles.

Benefits:

- Ensures top engine performance in all conditions, from cold starts to high-load situations and extreme temperatures
- High viscosity at hot engine
- Effectively fights deposits to keep engine parts and turbochargers clean
- Reduces engine wear during startup, even in harsh conditions
- Enhances fuel efficiency and extends engine life
- Suitable for both extended and regular oil change intervals
- Maintains oil quality over time
- Resists variable fuel quality and fuel dilution

Specifications and approvals:

BMW LONGLIFE-04

VW 502 00

VW 505 00

MB 229.5

MB 229.3

PORSCHE A40

RENAULT RN0700

RENAULT RN0710

RENAULT RN17

GM LL-A-025

GM LL-B-025

FIAT 9.55535-M2

FORD WSS-M2C937-A

CHRYSLER MS-10725

CHRYSLER MS-12633

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	70-90
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	12,5-16,3
Viscosity index	ASTM D 2270	-	> 150
Pour point	ASTM D 97	[°C]	< -35
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 7

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.