

**Technical Data for:**

**MAPETROL SPARCO COMPETITION SN 15W-40**

**Description:**

Mapetrol Sparco Competition SN 15W-40 is all-season, cost-effective, universal engine oil suitable for turbocharged and non-turbocharged petrol and diesel engines, including those with very high mileage, operating under diverse conditions. Designed to provide maximum protection in a wide range of vehicles, including passenger cars, light SUVs, minibuses, and light trucks. Not suitable for heavy trucks or similar vehicles.

**Benefits:**

- Compatible with all sealing materials, reducing the risk of leaks and ensuring the necessary oil pressure
- Lower oil consumption because of low volatility
- Ensures efficient engine performance in all conditions
- Provides long-lasting protection against wear, friction, and corrosion
- Ensures reliable lubrication of all engine components
- Excellent detergent and dispersing properties keep engine parts clean

**Specifications and approvals:**

API SN/CF  
ACEA A3/B4  
MB 229.1  
MB 229.3  
VW 501 00  
VW 500 00

VW 502 00  
VW 505 00  
PSA B71 2294  
RENAULT RN0700  
RENAULT RN0710

**Typical characteristics:**

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm <sup>3</sup> ]	0,85-0,95
Kinematic viscosity at 40 °C	ASTM D 445	[mm <sup>2</sup> /s]	100-120
Kinematic viscosity at 100 °C	ASTM D 445	[mm <sup>2</sup> /s]	12,5-16,3
Viscosity index	ASTM D 2270	-	> 130
Pour point	ASTM D 97	[°C]	< -24
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 9

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.