

**Technical Data for:**

**MAPETROL SPARCO PERFORMANCE WS2+ 0W-40**

**Description:**

Mapetrol Sparco Performance WS2+ 0W-40 is fully synthetic, ester enriched lubricant, meticulously formulated for sports cars, competitive machines, and high-powered engines. It is enriched with the remarkable benefits of WS2+ for superior performance and engine longevity.

**Benefits with WS2+ enhancement:**

- Offers an unrivaled level of engine purity, reducing harmful deposits and contaminants
- WS2+ fortifies your engine's endurance, granting it the ability to withstand even the most grueling racing conditions with grace and resilience
- WS2+ provides an unwavering shield against the most demanding of racing conditions
- Protects your engine's vital components, minimizing wear and tear

**Specifications and approvals:**

ACEA A3/B4	RENAULT RN0710
API SN/CF	RENAULT RN17
BMW LONGLIFE-04	GM LL-A-025
VW 502 00	GM LL-B-025
VW 505 00	FIAT 9.55535-M2
MB 229.5	FORD WSS-M2C937-A
MB 229.3	CHRYSLER MS-10725
PORSCHE A40	CHRYSLER MS-12633
RENAULT RN0700	

**Typical characteristics:**

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm <sup>3</sup> ]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm <sup>2</sup> /s]	70-90
Kinematic viscosity at 100 °C	ASTM D 445	[mm <sup>2</sup> /s]	12,5-16,3
Viscosity index	ASTM D 2270	-	> 150
Pour point	ASTM D 97	[°C]	< -35
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 7

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.