

Technical Data for:

MAPETROL SPARCO PERFORMANCE WS2+ 5W-50

Description:

Mapetrol Sparco Performance WS2+ 5W-50 is fully synthetic lubricant, meticulously formulated with premium base oils and enhanced with WS2+ for superior performance and engine longevity. It is designed for sports cars, competition, and high-powered engines, where performance and protection are of utmost importance.

Benefits with WS2+ enhancement:

- High viscosity at hot engine
- WS2+ contributes to reduced friction within your engine, which translates into better fuel efficiency and prolonged engine life
- WS2+ minimizes wear, reducing maintenance costs
- Excels in maintaining engine cleanliness and safeguarding critical components
- Optimized engine efficiency, leading to reduced fuel consumption, thereby helping you save on fuel expenses
- WS2+ ensures that your engine operates at the highest level of precision and protection

Specifications and approvals:

ACEA A3/B4

API SN/CF

MB 229.3

BMW LONGLIFE-01

VW 501 01

VW 505 00

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	95-130
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	16,3-21,9
Viscosity index	ASTM D 2270	-	> 170
Pour point	ASTM D 97	[°C]	< -30
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 9

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.