

Technical Data for:

MAPETROL SPARCO COMPETITION ESTER 2T

Description:

Mapetrol Sparco Competition Ester 2T is fully synthetic, ester-based lubricant specifically formulated to provide exceptional lubrication and engine protection. With its advanced ester technology and exceptional lubricity, it is an excellent choice for all owners of two-stroke engines.

Benefits:

- High viscosity ensures better lubrication and reduces engine wear and friction
- Gives exceptional performance at the maximum number of rpm
- Provides excellent engine cleanliness
- Protects the internal parts of the engine from corrosion, which extends the life of the engine

Specifications and approvals:

API TC

ISO-L-EGD

JASO FD

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,85–0,88
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	50-70
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	7-10
Viscosity index	ASTM D 2270	-	> 120
Pour point	ASTM D 97	[°C]	< -30
Flash point (Cleveland)	ASTM D 92	[°C]	> 100

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.