

Technical Data for:

MAPETROL SPARCO COMPETITION SCOOTER SYNTH 2T

Description:

Mapetrol Sparco Competition Scooter Synth 2T is fully synthetic oil specifically engineered for 2-stroke engines that operate in a wide range of conditions, from typical to extreme. It includes meticulously chosen additives to deliver excellent antiwear protection and minimize exhaust emissions, thanks to its "smokeless" technology, ensuring engine cleanliness.

Benefits:

- Ensures friction reduction
- Increases engine life duration and performance
- Formulated to go through all injector systems
- High thermal stability
- Self mixing
- Inhibits the accumulation of deposits
- Provides effective protection against corrosion

Specifications and approvals:

API TC

ISO-L-EGC

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,85–0,87
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	35-60
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	7-10
Viscosity index	ASTM D 2270	-	> 140
Pour point	ASTM D 97	[°C]	< -30
Flash point (Cleveland)	ASTM D 92	[°C]	> 150

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.