

Technical Data for:**MAPETROL MULTI VEHICLE GL 4+ 75W-80****Description:**

Mapetrol Multi Vehicle GL 4+ 75W-80 is high-quality, semi-synthetic, transmission oil designed for use in almost all passenger car manual gearboxes. It's particularly well-suited as a replacement for specific OEM original oils, simplifying gearbox oil selection and storage. It is recommended for all hypoid transmissions and it is suitable for spiral bevel gears, worm wheels, and most transaxles in all weather conditions.

Benefits:

- Ensures exceptionally smooth gear shifting with no vibrations
- Provides robust anti-wear protection, significantly extending the lifespan of transmissions
- Demonstrates proven resistance to oil degradation, resulting in extended oil life

Specifications and approvals:

API GL-4+	HONDA MTF 94	VW G 052 527
BMW 83220140516	NISSAN 999MP-MTF20P	VW G 052 726
BMW 83220309031	NISSAN MT-XZ	VW G 055 538
BMW MTF LT-2	PSA 9730 A2	TOYOTA JWS 227
FIAT 9.55550-MX3	PSA 9730 A8	HYUNDAI 02200-00130 TOD
FIAT 9.55550-MZ1	PSA B71 2330	LAND ROVER TYK500030
FORD ESD-M2C186-A	VOLVO 97308	SUBARU K0321-F0090
FORD WSS-M2C200-D2	VOLVO 97309	MAZDA MZ312644
GM 1940182	VOLVO 97310	MB 235.10
GM 1940768	VW G 052 171	

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,82-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	45-70
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	8,5-11,0
Viscosity index	ASTM D 2270	-	> 150
Pour point	ASTM D 97	[°C]	< -39
Flash point (Cleveland)	ASTM D 92	[°C]	> 200

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.