

Technical Data for:

MAPETROL PREMIUM SPORT 10W-60

Description:

Mapetrol Premium Sport 10W-60 is fully synthetic lubricant, formulated from cutting-edge, top-tier base oils, meticulously designed for the lubrication of all 4-stroke gasoline engines with multiple valves, and 4-stroke diesel engines, regardless of their turbocharger configuration.

Benefits:

- Very good fluidity at low temperature
- Outstanding engine cleanliness and durability
- Shear stability
- Wear protection
- High viscosity at hot engine

Specifications and approvals:

ACEA A3/B4

API SN/CF

BMW LONGLIFE-01

BMW M-MODELS

MB 229.3

VW 501 01

VW 505 00

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	150-170
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	21,9-26,1
Viscosity index	ASTM D 2270	-	> 190
Pour point	ASTM D 97	[°C]	< -33
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 9

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.