

Technical Data for:

MAPETROL PREMIUM 9000 SN 5W-40

Description:

Mapetrol Premium 9000 SN 5W-40 is fully synthetic lubricant suitable for all gasoline and diesel engines equipped with turbochargers and direct fuel injection. Its high-quality formulation enables extended drain intervals in accordance with manufacturer-specific requirements.

Benefits:

- Exceptional low-temperature fluidity
- Minimal resistance during startup
- Outstanding thermal stability
- Extended oil drain interval

Specifications and approvals:

API SN/CF
ACEA A3/B3
ACEA A3/B4
MB 229.1
VW 502 00
VW 505 00

Typical characteristics:

| Test | Method | Unit | Results |
|-------------------------------|-------------|----------------------|-----------|
| Density at 15 °C | ASTM D 4052 | [g/cm ³] | 0,80-0,90 |
| Kinematic viscosity at 40 °C | ASTM D 445 | [mm ² /s] | 75-95 |
| Kinematic viscosity at 100 °C | ASTM D 445 | [mm ² /s] | 12,5-16,3 |
| Viscosity index | ASTM D 2270 | - | > 160 |
| Pour point | ASTM D 97 | [°C] | < -36 |
| Flash point (Cleveland) | ASTM D 92 | [°C] | > 210 |
| T.B.N. | ASTM D 2896 | mg KOH/g | > 7 |

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.