

Technical Data for:

MAPETROL PREMIUM A5 V 0W-30

Description:

Mapetrol Premium A5 V 0W-30 is fully synthetic lubricant formulated with exceptionally high-quality base oils, custom-made to meet the specific requirements of Volvo's passenger cars. This oil is the recommended choice for the latest-generation Volvo Cars, including both gasoline and diesel models equipped with 5-cylinder engines.

Benefits:

- Enhances lubricating qualities
- Very good fluidity at low temperature
- Improves fuel efficiency
- Reduces fuel consumption and CO2 emissions
- Extends the engine's lifespan

Specifications and approvals:

API SN/CF

ACEA A5/B5

VOLVO VCC 95200377

BMW LONGLIFE-01 FE

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	50-70
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	9,3-12,5
Viscosity index	ASTM D 2270	-	> 160
Pour point	ASTM D 97	[°C]	< -35
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 7

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.